

3M

SCOTT™

Engineered for this event.



3M™ Scott™ ELSA™
Emergency Escape
Breathing Device - N

3MScott.com/ELSA

Upgrade your escape device.

When an emergency occurs, and you have to escape safely, you can rely on the 3M™ Scott™ ELSA™ Emergency Escape Breathing Device - N. Designed for the demands of industrial environments, it's the one you want wherever IDLH or other hazardous conditions may occur. Its one-size-fits-all hood features 360° visibility. The respirator is available in 5-, 10- and 15-minute durations and meets SOLAS¹ chapter II-2, part D requirements.

Get the one that's easy to train, easy to use and gets you to safety.

Fully-enclosed, chemically-resistant bag reduces dirt and debris.

Large tab aids in one-step, pull-to-open operation for quick donning.

Integrated carry handle and strap enables multiple carrying options.



¹10 and 15 minute variants



One size fits all.²



Easily fits over safety glasses and can be used with facial hair.



Simply pull hood over head – no additional securing required.

Cost effective.

- ▶ Fits in common third party wall cases
- ▶ No shelf life limit when used, maintained and serviced according to instructions
- ▶ 3-year warranty

Easy to train and easy to use.

- ▶ Training poster available
- ▶ Training video available



²per Zhuang & Bradtmiller (2005): Head-and-Face Anthropometric Survey of U.S. Respirator Users

Get to know ELSA™ EEBD - N at [3MScott.com](https://www.3MScott.com).

3M™ Scott™ ELSA™ Emergency Escape Breathing Device - N



			
Specifications	5 Minute	10 Minute	15 Minute
Operating Pressure	2,216 psi	3,000 psi	3,000 psi
Cylinder Composition	Aluminum	Aluminum	Aluminum
Weight (full), lbs	6.6	10.0	12.0
Weight (Drained), lbs	6.0	8.9	10.3
Cylinder Hydrostatic test frequency	5 years	5 years	5 years
Shelf life	Indefinite ¹	Indefinite ¹	Indefinite ¹
Approvals	NIOSH	NIOSH	NIOSH
Other	—	SOLAS ²	SOLAS ²
Flame resistant hood	Yes	Yes	Yes
Approximate escape route (Estimating 4 mph walking speed on a flat surface)	1760 ft (1/3 mile)	3520 ft (2/3 mile)	5280 ft (1 mile)

¹ When used, maintained and serviced according to instructions

² Meets SOLAS Chapter II-2, Part D requirements

3M™ Scott™ ELSA™ EEBD - N Ordering Information

Part Number	Description
8007212	ELSA EEBD 5 Min-N
8007213	ELSA EEBD 10 Min-N
8007214	ELSA EEBD 15 Min-N
8007212-D	ELSA EEBD 5 Min-N, Drained
8007213-D	ELSA EEBD 10 Min-N, Drained
8007214-D	ELSA EEBD 15 Min-N, Drained
Part Number	Spare Parts
8007196	ELSA Carry Bag Assy, 5 Min-N
8007197	ELSA Carry Bag Assy, 10 Min-N
8007198	ELSA Carry Bag Assy, 15 Min-N
8007204	ELSA EEBD - N Replacement Hood w/Diffuser
8007210	ELSA EEBD - N Replacement Carry Strap
2010173	Anti Fog Wipe
595398-01	ELSA User Instructions-N
2007294	Cylinder Fill Port Dust Covers (10/pkg)

For technical use and application questions regarding these products, contact the 3M Technical Service Hotline at 1-800-243-4630. For service and repair questions contact 3M Scott at 1-800-247-7257.



These respirators help to protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of applicable jurisdiction, as appropriate. Improper use may result in sickness or death. For correct use, see supervisor and User Instructions, or call 3M PSD Technical Service in USA at 1-800-243-4630 and in Canada at 1-800-267-4414.



3M™ Scott™ Fire & Safety
Personal Safety Division
Monroe Center, P.O. Box 569
Monroe, NC 28110

3M PSD products are for occupational use only.
Web: 3MScott.com

Please recycle. Printed in USA.
3M, Scott and ELSA are trademarks of 3M.
© 3M 2020. All rights reserved.